

**SEMI SYNTHETIC
10W-40 A3**

Semi Synthetic 10w-40, A3 B4

Autonoe Part Numbers: **AUT007020** (20L) **AUT007199** (199L)

PRODUCT DESCRIPTION

A fuel-efficient multi-grade engine oil manufactured from a precisely balanced blend of top quality mineral and synthetic base stocks and performance enhancing additives. The high lubricity of this product provides lower internal friction for reduced engine wear while the relatively low viscosity improves flow rates and hydraulic tappet performance during cold start and engine idling.

FEATURES & BENEFITS

Autonoe High Performance ensures outstanding performance in the following areas:

- Semi-synthetic formulation.
- Stay in grade properties.
- Excellent high and low temperature stability.
- Improved fuel efficiency.
- Improved oil consumption and emissions.
- Superior performance to mineral based oils.

PERFORMANCE/ SPECIFICATIONS

Suitable for normally aspirated, turbocharged engines and engines that run on petrol or diesel fuels. Suitable applications include passenger cars and light commercials particularly modern vehicles. Miscible with synthetic and mineral based engine oils.

Autonoe Recommended for

ACEA A3/B3, A3/B4
API SN/CF
MB 229.1, 229.3
Renault 0700, 0710
VW 501.01/ 505.00

TYPICAL PROPERTIES

Kinematic Viscosity @ 40 deg. C	95.51
Kinematic Viscosity @ 100 deg. C	13.82
Viscosity Index	147
Total Base Number (mg KOH/g)	10.3
Flash Point, deg. C	220
Density @ 15°C	0.871

These data are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.