

SEMI SYNTHETIC 5W-30, A1/B1

Semi Synthetic 5W-30, A1/B1

Autonoe Part Numbers: **AUT008020** (20L) **AUT008199** (199L)

PRODUCT DESCRIPTION

Semi Synthetic 5w-30 ACEA A1/B1 is a fuel-efficient multi-grade engine oil manufactured from a precisely balanced blend of top quality mineral and synthetic base stocks and performance enhancing additives. The high lubricity of Semi Synthetic 5w-30 ACEA A1/B1 provides lower internal friction for reduced engine wear while the relatively low viscosity improves flow rates and hydraulic tappet performance during cold start and engine idling.

FEATURES & BENEFITS

Autonoe High Performance ensures outstanding performance in the following areas:

- Semi-synthetic formulation.
- Stay in grade properties.
- Excellent high and low temperature stability.
- Improved fuel efficiency.
- Improved oil consumption and emissions.
- Superior performance to mineral based oils.

PERFORMANCE/ SPECIFICATIONS

Suitable for normally aspirated and turbocharged engines. Suitable for engines that run on petrol or diesel fuels. Applications include passenger cars and light commercials particularly modern vehicles. Semi Synthetic 5W-30 ACEA A1/B1 is miscible with synthetic and mineral based engine oils.

Autonoe Recommended for
ACEA A1/B1, A5/B5
API SL/CF
Ford WSS-M2C913-B
ILSAC GF-3

TYPICAL PROPERTIES

Density @ 15°C	0.857
Flash Point (°C)	212
Kinematic Viscosity cSt @ 100°C	10.5
Kinematic Viscosity cSt @ 40°C	66.4
Pour Point (°C)	-44
Total Base Number (mg KOH/g)	9.20
Viscosity Index	146

These data are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.