

SYNTEC PRO
5w30 C4
Synthetic engine Oil

Syntec Pro 5w-30 C4

Autonoe Part Numbers: **AUT011020** (20L) **AUT011199** (199L)

PRODUCT DESCRIPTION

A low SAPS, fully synthetic, multi-grade engine oil. Advanced additive technology ensures optimum performance of engine components, including diesel particulate filters (DPF) and three way catalysts (TWC) systems, where present. Formulated to provide long term protection to emission control systems. Protecting these systems helps to maintain optimal emissions cleanliness throughout the life cycle of an engine, increasing environmental friendliness.

FEATURES & BENEFITS

Autonoe High Performance ensures outstanding performance in the following areas:

- Effective environmental protection.
- Maintains performance over extended drain intervals.
- Increased fuel efficiency.
- High standards of engine cleanliness.
- Long term anti-wear and oxidation stability.
- Excellent high and low temperature performance.

PERFORMANCE/ SPECIFICATIONS

Specifically engineered to meet the performance demands of modern OEM manufacturers. Suited to applications where high standards of emission control are required under all conditions including those of vigorous, high speed styles of driving.

Autonoe Recommended for
ACEA C4
MB 226.51
Renault RN 0720

TYPICAL PROPERTIES

Density @ 15°C	0.851
Flash Point (°C)	212
Kinematic Viscosity cSt @ 100°C	12
Kinematic Viscosity cSt @ 40°C	69
Pour Point (°C)	-45
Total Base Number (mg KOH/g)	6.0
Viscosity Index	172

These data are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.