

SYNTEC PRO
5w-30 FMC 913-D
Synthetic Engine Oil

Syntec Pro 5w-30 FMC 913-D

Autonoe Part Numbers: **AUT012020** (20L) **AUT012020** (199L)

PRODUCT DESCRIPTION

Synthetic 5w-30 FMC 913-D is a new generation, fully synthetic multi-grade engine oil formulated for use with a variety of OEM engines, such as those manufactured by Ford. The careful selection of high quality base oils, use of the latest advancements in chemical engineering and additive technology, coupled with rigorous bench testing have enabled Synthetic 5w-30 FMC 913-D to set new standards in engine oil performance. Synthetic 5w-30 FMC 913-D has been developed to provide outstanding performance, superior soot handling, extended drain intervals, improved fuel economy and greater robustness to the use of fuels containing increased levels of bio-diesel.

FEATURES & BENEFITS

Autonoe High Performance ensures outstanding performance in the following areas:

- Greater robustness to bio fuels.
- Ensures lubricant performance over extended drain intervals.
- Maintains very high standards of engine cleanliness.
- Exceptional long-term anti-wear and oxidation stability.
- Superior performance under both high temperature and low temperature conditions.
- Excellent start up protection.
- Improved fuel efficiency.

PERFORMANCE/ SPECIFICATIONS

Synthetic 5w-30 FMC 913-D is meticulously engineered to meet modern demands for performance for a wide range of Ford and other OEM petrol and diesel engines whilst meeting Euro IV/V emissions standards.

Autonoe Recommended for

ACEA A5/B5
API SN/CF
BMW LL-01 FE
Ford WSS-M2C913-C/D
Renault RN0700
JLR STJLR.03.5003

TYPICAL PROPERTIES

Density @ 15°C	0.854
Flash Point (°C)	225
Kinematic Viscosity cSt @ 100°C	10.1
Kinematic Viscosity cSt @ 40°C	57.4
Pour Point (°C)	-45
Total Base Number (mg KOH/g)	10.0
Viscosity Index	165

These data are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.