

**SYNTEC PRO**  
**5w/40, A3/B4**  
Synthetic Engine Oil

**Syntec Pro 5W/40, A3/B4**

Autonoe Part Numbers: **AUT014020** (20L) **AUT014199** (199L)

**PRODUCT DESCRIPTION**

A fully synthetic engine oil formulated from high quality synthetic base stocks and advanced performance improving additives, to deliver outstanding performance and durability for the most demanding motorist. Excellent low temperature properties ensure the oil circulates rapidly, improving cold starting and provides excellent lubricity to reduce internal friction during operation.

**FEATURES & BENEFITS**

Autonoe High Performance ensures outstanding performance in the following areas:

- Ensures lubricant performance over extended drain intervals.
- Maintains very high standards of engine cleanliness.
- Long term anti-wear and oxidation stability.
- Superior performance at high temperature and low temperature conditions.
- Excellent start up protection.
- Improved fuel efficiency.

**PERFORMANCE/ SPECIFICATIONS**

Suitable for use in most petrol and diesel engines with or without turbochargers. For passenger cars and light commercial vehicles operating in all driving conditions. Synthetic 5W-40 ACEA A3/B4 is miscible with all synthetic and mineral based engine oils.

**Autonoe Recommended for**

ACEA A3/B3, A3/B4  
API SL/CF  
BMW LL-01  
Fiat 9.55535-M2  
GM-LL- B-025  
MB 229.3, 229.5  
Porsche A40  
PSA B71 2296  
Renault RN0710  
VW 502.00/ 505.00

**TYPICAL PROPERTIES**

Density @ 15°C	0.849
Flash Point (°C)	223
Kinematic Viscosity cSt @ 100°C	14.73
Kinematic Viscosity cSt @ 40°C	93.05
Pour Point (°C)	-40
Total Base Number (mg KOH/g)	10.4
Viscosity Index	166

These data are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.