

SYNTEC PRO
5w/40 PD 505.01

Synthetic Engine Oil

Syntec Pro, 5w/40 PD 505.01

Autonoe Part Numbers: **AUT017020** (20L) **AUT017199** (199L)

PRODUCT DESCRIPTION Formulated from fully synthetic base oils and precisely measured high performance additives. This oil is engineered for VW, AUDI, SEAT, Skoda and Ford diesel engines, including those fitted with VW 505.01 Pumpe Düse (PD) diesel injector systems.

FEATURES & BENEFITS Autonoe High Performance ensures outstanding performance in the following areas:

- Provides engine protection under high performance demands.
- Low and high operating temperatures.
- System efficiency.
- Improves fuel economy.
- Suitable for engines requiring the 505.01 performance standard.

PERFORMANCE/ SPECIFICATIONS Meticulously developed for use with various Volkswagen, Audi, SEAT, Skoda, and Ford diesel car and light van engines, including those fitted with Pumpe Düse (PD) engine – specification VW 505.01.

Autonoe Recommended for

ACEA C3
API SN/CF
BMW LL-04
Fiat 9.55535-S2
Ford WSS-M2C917-A
GM Dexos 2
MB 229.31, 229.51
Porsche A40
VW 502.00/ 505.01

| | | |
|---------------------------|---------------------------------|-------|
| TYPICAL PROPERTIES | Density @ 15°C | 0.847 |
| | Flash Point (°C) | 230 |
| | Kinematic Viscosity cSt @ 100°C | 14.2 |
| | Kinematic Viscosity cSt @ 40°C | 92.0 |
| | Pour Point (°C) | -42 |
| | Total Base Number (mg KOH/g) | 8.5 |
| | Viscosity Index | 159 |

These data are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.