



## Syntec Pro 0w-30, C3

Autonoe Part Numbers: **AUT019020** (20L) **AUT019199** (199L)

PRODUCT DESCRIPTION

fully synthetic, high performance engine oil for passenger cars designed to meet the thorough demands imposed by many of the modern petrol and diesel car engines. Designed for modern engines that require a high level of protection in cold conditions.

## FEATURES & BENEFITS

Autonoe High Performance ensures outstanding performance in the following areas:

- Long service intervals.
- Improved performance and fuel efficiency.
- Low temperature performance.
- Supreme levels of engine protection.

## PERFORMANCE/ SPECIFICATIONS

Suitable for use in engines where the manufacturer recommends ACEA C3 or API SN in passenger car petrol and diesel engines.

**Autonoe Recommended for** 

ACEA C3 API SN/CF BMW LL-04 GM Dexos 2 MB 229.31

VW 502.00/ 505.01

## TYPICAL PROPERTIES

Density @ 15°C	0.843	
Flash Point (°C)	210	
Kinematic Viscosity cSt @ 100°C	12.2	
Kinematic Viscosity cSt @ 40°C	73	
Pour Point (°C)	-50	
Total Base Number (mg KOH/g)	8	
Viscosity Index	165	

These data are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.