

SYNTEC PRO
5w-30, C1
Synthetic Engine Oil

Syntec Pro 5w-30, C1

Autonoe Part Numbers: **AUT020020** (20L) **AUT020199** (199L)

PRODUCT DESCRIPTION

A low SAPS, fully synthetic, multi-grade engine oil. The application of advanced additive technology ensures optimum performance of engine components. Formulated to provide long term protection to emission control systems, maintaining optimal cleanliness throughout the life cycle of an engine, and increasing environmental friendliness.

FEATURES & BENEFITS

Autonoe High Performance ensures outstanding performance in the following areas:

- Effective environmental protection.
- Maintains performance over extended drain intervals.
- Increased fuel efficiency.
- High standards of engine cleanliness.
- Long term anti-wear and oxidation stability.
- Excellent high and low temperature performance.

PERFORMANCE/ SPECIFICATIONS

Formulated for use in turbocharged and normally aspirated diesel and petrol engines. Low levels of sulphated ash, phosphorus and sulphur enable this synthetic engine oil to provide protection to after treatment systems such as diesel particulate filters.

Autonoe Recommended for

ACEA C1
Ford WSS-M2C934-B
JLR STJLR.03.5005

TYPICAL PROPERTIES

| | |
|---------------------------------|-------|
| Density @ 15°C | 0.845 |
| Flash Point (°C) | 230 |
| Kinematic Viscosity cSt @ 100°C | 9.85 |
| Kinematic Viscosity cSt @ 40°C | 53.5 |
| Pour Point (°C) | -43 |
| Total Base Number (mg KOH/g) | 5.8 |
| Viscosity Index | 173 |

These data are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.