

SYNTEC PRO
0w-20, SN/SF
Synthetic Engine Oil

Autonoe
The Professional Choice

Syntec Pro 0w-20, SN/CF

Autonoe Part Numbers: **AUT028020** (20L) **AUT028199** (199L)

PRODUCT DESCRIPTION

A synthetic, high quality engine oil formulated to meet the demands of modern passenger car engines. Formulated from high quality base stocks and advanced performance enhancing additives to deliver exceptional resistance to thermal breakdown, outstanding low temperature fluidity, excellent engine wear protection and deposit formation, even under the most severe driving conditions. It designed to meet the demanding conditions found in modern diesel engines.

FEATURES & BENEFITS

Autonoe High Performance ensures outstanding performance in the following areas:

- Improved performance and fuel efficiency.
- Long service intervals.
- Low temperature performance.
- Outstanding protection against wear, rust and corrosion.

PERFORMANCE/ SPECIFICATIONS

Suitable for use with many of the latest petrol engines used by OEMs such as Honda, Toyota, Mazda and Suzuki. Designed to be used where an 0w-20 grade is required to meet certain API, ILSAC and other specifications.

Autonoe Recommended for

API SN/CF
Chrysler MS-6395
ILSAC GF-5
Volvo VCC RBS0-2AE

TYPICAL PROPERTIES

Density @ 15°C	0.844
Flash Point (°C)	200
Kinematic Viscosity cSt @ 100°C	8.8
Kinematic Viscosity cSt @ 40°C	48
Pour Point (°C)	-48
Total Base Number (mg KOH/g)	8
Viscosity Index	165

These data are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.