

SYNTEC PRO
5w-30, C2
 Synthetic Engine Oil

Syntec Pro 5w-30, C2

Autonoe Part Numbers: **AUT029020** (20L) **AUT029199** (199L)

PRODUCT DESCRIPTION

A fully synthetic multi-grade engine oil. Advanced additive technology utilised in this product ensures optimum performance of engine components, including diesel particulate filters (DPF) where present. Formulated to provide long term protection to emission control systems. Protecting these systems helps to maintain optimal emissions cleanliness throughout the life cycle of an engine, increasing environmental friendliness.

FEATURES & BENEFITS

Autonoe High Performance ensures outstanding performance in the following areas:

- Effective environmental protection.
- Maintains performance over extended drain intervals.
- Increased fuel efficiency.
- High standards of engine cleanliness.
- Long term anti-wear and oxidation stability.
- Excellent high and low temperature performance.

PERFORMANCE/ SPECIFICATIONS

Specifically engineered to meet the performance demands and OEM requirements of modern petrol and diesel engines. Well suited to applications, where high standards of emission control are required under all conditions - including those of vigorous, high speed styles of driving.

Autonoe Recommended for

ACEA C2
 API SN/CF
 Fiat 9.55535-S1
 PSA B71-2290

TYPICAL PROPERTIES

Density @ 15°C	0.846
Flash Point (°C)	212
Kinematic Viscosity cSt @ 100°C	10.0
Kinematic Viscosity cSt @ 40°C	58.0
Pour Point (°C)	-45
Total Base Number (mg KOH/g)	7.8
Viscosity Index	160

These data are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.