The Professional Choice

Synthetic Engine Oil

Syntec Pro 5w-20 FMC 948-B

Autonoe Part Numbers: AUT030020 (20L) AUT030199 (199L)

PRODUCT DESCRIPTION

A fully synthetic engine oil formulated from high quality base stocks and advanced performance enhancing additives. Developed to provide exceptional resistance to thermal breakdown, outstanding low temperature fluidity, and excellent engine protection against wear and deposit formation under the most severe driving conditions.

FEATURES & BENEFITS

Autonoe High Performance ensures outstanding performance in the following areas:

- Outstanding protection against wear, rust and corrosion.
- Excellent thermal stability.
- Superior oxidation resistance.
- Long service intervals.
- Increases fuel economy.
- Improves low temperature performance.

PERFORMANCE/ SPECIFICATIONS

Suitable for use with wide variety of modern passenger car, SUV and light van engines requiring a 5W-20 grade, including Ford EcoBoost petrol engines.

Autonoe Recommended for

API SN/ CF

Ford WSS-M2C948-B

ILSAC GF 5

TYPICAL PROPERTIES

Density @ 15°C	0.845
Flash Point (°C)	233
Kinematic Viscosity cSt @ 100°C	8.3
Kinematic Viscosity cSt @ 40°C	45.1
Pour Point (°C)	-48
Total Base Number (mg KOH/g)	7.9
Viscosity Index	161

These data are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.