

Syntec Pro 0w-30, A5/B5

FEATURES &

Autonoe Part Numbers: AUT037020 (20L) AUT037199 (199L)

PRODUCT
DESCRIPTIONA fully synthetic high-performance engine oil for passenger cars designed to meet the thorough
demands of many current petrol and diesel car engines. It has been formulated for use where the
A5/B5 specification is specified, as recommended by vehicle manufactures such as Volvo.
A sophisticated blend of synthetic base oil, pour point depressant, viscosity modifier and a unique
additive package delivers outstanding performance.

Autonoe High Performance ensures outstanding performance in the following areas:

BENEFITS Improved performance and fuel efficiency. Long service intervals. Low temperature performance. Supreme levels of engine protection. PERFORMANCE/ This engine oil is suitable for use engines where the manufacturer recommends an ACEA A1/B1, A5/B5 in passenger car petrol and diesel engines. Autonoe Recommended for ACEA A5/B5, A1/B1

API SL/CF BMW LL-01FE

TYPICAL PROPERTIES	Density @ 15°C	0.843
	Flash Point (°C)	210
	Kinematic Viscosity cSt @ 100°C	10.0
	Kinematic Viscosity cSt @ 40°C	53.5
	Pour Point (°C)	-50
-	Total Base Number (mg KOH/g)	10
	Viscosity Index	177

These data are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.