

SYNTEC PRO
0w-30, C2
Synthetic Engine Oil

Syntec Pro 0w-30, C2

Autonoe Part Numbers: **AUT040020** (20L) **AUT040199** (199L)

PRODUCT DESCRIPTION

A fully synthetic, high performance engine oil for passenger cars designed to meet the thorough demands imposed by many of the modern petrol and diesel car engines. Designed for modern engines that require a high level of protection in cold conditions.

FEATURES & BENEFITS

Autonoe High Performance ensures outstanding performance in the following areas:

- Long service intervals.
- Improved performance and fuel efficiency.
- Low temperature performance.
- Supreme levels of engine protection.

PERFORMANCE/ SPECIFICATIONS

Suitable for use in engines where the manufacturer recommends and ACEA C2 or API SN in passenger car petrol and diesel engines.

Autonoe Recommended for

ACEA C2
API SN/CF
BMW LL-12FE
Ford WSS-M2C950-A
JLR STJLR.03.5007

TYPICAL PROPERTIES

Density @ 15°C	0.843
Flash Point (°C)	210
Kinematic Viscosity cSt @ 100°C	9.6
Kinematic Viscosity cSt @ 40°C	53
Pour Point (°C)	-52
Total Base Number (mg KOH/g)	7.8
Viscosity Index	168

These data are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.