

Syntec 0w-30 PSA

Autonoe Part Numbers: AUT043020 (20L) AUT043199 (199L)

PRODUCT DESCRIPTION	A fully synthetic high-performance engine oil for passenger cars designed to meet the thorough demands of many current petrol and diesel car engines providing improved fuel economy. Designed for modern engines that require a high level of protection in cold conditions.		
FEATURES & BENEFITS	 Autonoe High Performance ensures outstanding performance in the following areas: Long service intervals. Improved performance and fuel efficiency. Low temperature performance. Supreme levels of engine protection. 		
PERFORMANCE/ SPECIFICATIONS	Suitable for use in engines where the manufacturer recommends and ACEA C2 or PSA B71 2312 in passenger car petrol and diesel engines. Autonoe Recommended for ACEA C2 PSA B71 2312		
TYPICAL PROPERTIES	Density @ 15°C	0.845	
	Flash Point (°C)	200	
	Kinematic Viscosity cSt @ 100°C	9.7	
	Kinematic Viscosity cSt @ 40°C	54	
	Pour Point (°C)	-52	
	Total Base Number (mg KOH/g)	6.1	
	Viscosity Index	167	

These data are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.