

UTTO AGRITECH
SUPER TRACTOR OIL

UTTO Universal Agritech Tractor Oil

Autonoe Part Numbers: **ATR032020** (20L) **ATR032199** (199L) **ATR0321000** (1000L)

PRODUCT DESCRIPTION

A premium universal transmission and hydraulic fluid, specifically designed for use in agricultural power transmissions, hydraulics and rear axles including oil immersed wet brakes. Using high quality base oils and exceptional additive technology to provide an advanced lubricant which demonstrates excellent performance characteristics against various stringent test requirements of major equipment manufacturers'

FEATURES & BENEFITS

Autonoe High Performance ensures outstanding performance in the following areas:

- Allows for rationalisation of products.
- Good resistance against aeration & foaming.
- Engineered to have good oxidation resistance, thermal stability and superb low temperature performance.
- Excellent brake squawk and chatter suppression.
- Exceptional anti-wear properties.
- Provides constant frictional performance.
- Suitable to use where API GL-4 SAE 10W-30 or SAE 80W is required.

PERFORMANCE/ SPECIFICATIONS

Recommended by Autonoe as suitable for the following applications:

API GL-4
AGCO/Allis 821 XL
Allison C4
Case MS 1204/1206/1207
Case New Holland MAT 3525
Caterpillar TO-2
Denison HF-0/1/2
Ford M2C86-B/C, M2C134-D
John Deere J20C
Komatsu AXO 80
Kubota UDT
Massey Ferguson M1127A, M1135, M1143, M1145
New Holland 410B
Sperry Vickers M-230-S, M-2950-S, I-280-S
Volvo WB101
ZF TE-ML 03E, 05F, 06K, 17E, 21F

UTTO AGRITECH
SUPER TRACTOR OIL

**TYPICAL
PROPERTIES**

| | | |
|--|-------------------|-------|
| Density @ 15°C (kg/m ³) | ASTM D4052 | 0.868 |
| Flash Point (°C) | ASTM D92 | >190 |
| Kinematic Viscosity @ 40°C (mm/s ²) | ASTM D445 | 69 |
| Kinematic Viscosity @ 100°C (mm/s ²) | ASTM D445 | 10.7 |
| Pour Point (°C) | ASTM D97 | -35 |
| Viscosity Index | ASTM D2207 | 144 |

These data are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.