

SYNTEC ISO22

Compressor & Hydraulic Oil

Syntec ISO22 Compressor & Hydraulic Oil

Autonoe Part Numbers: **AUTCMP001020** (20L) **AUTCMP001199** (199L) **AUTCMP0011000** (1000L)

PRODUCT DESCRIPTION Blended from carefully selected base oils with high performance additive technology for extended 4000hrs service intervals. Specially designed to have a very low tendency to form carbon whilst being fortified to inhibit wear, corrosion, oxidation, and foaming.

FEATURES & BENEFITS Autonoe High Performance ensures outstanding performance in the following areas:

- Demulsifying to ensure rapid water separation.
- Excellent anti-wear characteristics.
- Good anti-foam and air release properties.
- Outstanding corrosion protection.
- Superior oxidation resistance to provide a long service life.

PERFORMANCE/SPECIFICATIONS Recommended by Autonoe as suitable for the following applications:

ANFOR NF E 48-603
BS 489
Cincinnati P38
Dennison HF-0
DIN 51354 Stage 11
DIN 51506 VD-L
DIN 51524 Part II
DP 6521 DAA/DAB/DAG/DAH

TYPICAL PROPERTIES	Density @ 15°C (kg/m3)	ASTM D4052	0.85
	Flash Point (°C)	ASTM D92	>130
	Kinematic Viscosity @ 40°C (mm/s ²)	ASTM D445	22
	Kinematic Viscosity @ 100°C (mm/s ²)	ASTM D445	4.3
	Pour Point (°C)	ASTM D97	<-10
	Viscosity Index	ASTM D2207	95
	Copper Corrosion	ASTM D130	Pass
	Demulsibility	ASTM D1401	40-40-0
	Oxidation	ASTM D943	4000hrs
	Appearance		Straw/light amber liquid

These data are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.