

SYNTEC ISO68

## Compressor & Hydraulic Oil

### Syntec ISO68 Compressor & Hydraulic Oil

Autonoe Part Numbers: **AUTCMP006020** (20L) **AUTCMP006199** (199L) **AUTCMP00601000** (1000L)

**PRODUCT DESCRIPTION** Blended from carefully selected base oils with high performance additive technology for extended 4000hrs service intervals. Specially designed to have a very low tendency to form carbon whilst being fortified to inhibit wear, corrosion, oxidation, and foaming.

**FEATURES & BENEFITS** Autonoe High Performance ensures outstanding performance in the following areas:

- Demulsifying to ensure rapid water separation.
- Excellent anti-wear characteristics.
- Good anti-foam and air release properties.
- Outstanding corrosion protection.
- Superior oxidation resistance to provide a long service life.

**PERFORMANCE/SPECIFICATIONS** Recommended by Autonoe as suitable for the following applications:

ANFOR NF E 48-603  
BS 489  
Cincinnati P54  
Dennison HF-0  
DIN 51354 Stage 11  
DIN 51506 VD-L  
DIN 51524 Part II  
DP 6521 DAA/DAB/DAG/DAH

<b>TYPICAL PROPERTIES</b>	Density @ 15°C (kg/m3)	<b>ASTM D4052</b>	0.87
	Flash Point (°C)	<b>ASTM D92</b>	>200
	Kinematic Viscosity @ 40°C (mm/s <sup>2</sup> )	<b>ASTM D445</b>	68
	Kinematic Viscosity @ 100°C (mm/s <sup>2</sup> )	<b>ASTM D445</b>	8.8
	Pour Point (°C)	<b>ASTM D97</b>	<-25
	Viscosity Index	<b>ASTM D2207</b>	102
	Copper Corrosion	<b>ASTM D130</b>	Pass
	Demulsibility	<b>ASTM D1401</b>	40-40-0
	Oxidation	<b>ASTM D943</b>	4000hrs
	Appearance		Straw/light amber liquid

These data are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.